



# Auxiliary Cables

**The Extra Power You Need!**

- For ISO or auxiliary applications
- Reduce signal noise - ISOCOIL™ and ISOFLEX™ feature a twisted pair of brown and green wires which reduce signal noise
- Spring-wrapped compression contact pins
- Male ground pin to prevent mis-connections
- Heavy duty, reinforced zinc die-cast plugs

## ISOCOIL™



1/8, 2/10 & 4/12 ga.

<b>31-9323</b>	12', with zinc diecast plugs
<b>31-9623</b>	15', with zinc diecast plugs
<b>31-9923</b>	15', 48" lead, with zinc diecast plugs

- Flexible from -82°F to 195°F (-63°C to 91°C)
- Excellent recoil memory, chemical and abrasion resistance
- Twisted pair brown & green wires reduces signal noise

## ISOFLEX™



1/8, 2/10 & 4/12 ga.

<b>31-2033</b>	10', with zinc diecast plugs
<b>31-2053</b>	12', with zinc diecast plugs
<b>31-2073</b>	15', with zinc diecast plugs
<b>31-2093</b>	20', with zinc diecast plugs

- Good chemical and abrasion resistance
- Twisted pair brown & green wires reduces signal noise

## Accessory Cable



1/8, 2/10 & 4/12 ga.

<b>31-4323</b>	12', with zinc diecast plugs
<b>31-4623</b>	15', with zinc diecast plugs

- Flexible from -82°F to 195°F (-63°C to 91°C)
- Good recoil memory , chemical and abrasion resistance
- Brown & green wires are not twisted