

# LIFTGATE CHARGING CABLES

- For liftgate applications utilizing a trailer battery pack
- 4 ga. fine stranded copper for flexibility
- 100 amp continuous capacity; 200 amp intermittent capacity



## Dual Pole



<a href="#">23-2326</a>	12', 1 ground, 1 hot	*
<a href="#">23-2626</a>	15', 1 ground, 1 hot	*
<a href="#">23-2926</a>	15', with 48" lead, 1 ground, 1 hot	*

- Excellent recoil memory, chemical and abrasion resistance
- Flexible from -82°F to 195°F (-63°C to 91°C)
- Internal ground to improve ground connections
- Heavy duty, reinforced zinc die-cast plugs
- Mates with dual pole metal socket 15-326

## Dual Pole PERMACOIL™



<a href="#">23-2316</a>	12', 1 ground, 1 hot	*
<a href="#">23-2616</a>	15', 1 ground, 1 hot	*
<a href="#">23-2916</a>	15', with 40" lead, 1 ground, 1 hot	*

- Good recoil memory, chemical and abrasion resistance
- Flexible from -87°F to 150°F (-66°C to 66°C)
- Internal ground to improve ground connections
- Mates with dual pole metal socket 15-326
- Same heavy duty jacket as our PERMACOIL™ and ABS PERMACOIL™

## Dual Pole “Y” Adapter



<a href="#">23-2630</a>	15', with 48" and 24" leads, 1 ground, 1 hot	*
-------------------------	--	---

- For fleets with single and dual pole trailers
- Allows dual pole tractor to connect to single or dual pole trailer
- Coil has dual pole tractor side and dual and single pole plug trailer side
- Excellent recoil memory, chemical and abrasion resistance
- Flexible from -82°F to 195°F (-63°C to 91°C)
- Heavy duty, reinforced zinc die-cast housing

\* Working length - As measured by pull force per SAE J2222. Length of actual cable is significantly longer.

## Dual Pole to Single Pole Lead



<a href="#">23-2628</a>	15', 1 ground, 1 hot	*
-------------------------	----------------------	---

- Coil has one dual pole and one single pole plug
- Excellent recoil memory, chemical and abrasion resistance
- Flexible from -82°F to 195°F (-63°C to 91°C)
- Heavy duty, reinforced zinc die-cast housing

## Single Pole



<a href="#">23-4325</a>	12', 1 hot	*
-------------------------	------------	---

<a href="#">23-4625</a>	15', 1 hot	*
-------------------------	------------	---

<a href="#">23-4925</a>	15', with 48" lead, 1 hot	*
-------------------------	---------------------------	---

- Good recoil memory, chemical and abrasion resistance
- Flexible from -87°F to 150°F (-66°C to 66°C)
- Heavy duty, reinforced zinc die-cast plugs
- Mates with single pole metal socket 15-320

## Straight - Dual Pole



<a href="#">23-2251</a>	12', 1 ground, 1 hot	
-------------------------	----------------------	--

<a href="#">23-2271</a>	15', 1 ground, 1 hot	
-------------------------	----------------------	--

<a href="#">23-2291</a>	20', 1 ground, 1 hot	
-------------------------	----------------------	--

- Good chemical and abrasion resistance
- Internal ground to improve ground connection
- Heavy duty, reinforced zinc die-cast plugs
- Mates with 15-326 socket

## Straight - Single Pole



<a href="#">23-2051</a>	12', 1 hot	
-------------------------	------------	--

<a href="#">23-2071</a>	15', 1 hot	
-------------------------	------------	--

<a href="#">23-2091</a>	20', 1 hot	
-------------------------	------------	--

- Good chemical and abrasion resistance
- Heavy duty, reinforced zinc die-cast plugs
- Mates with 15-320 socket

\* Working length - As measured by pull force per SAE J2222. Length of actual cable is significantly longer.