PHILIPS

THE STRONGEST CABLE WITH CONTINUOUS LIFE... For an uninterrupted ride!



Anatomy of a QCP™ (Quick-Connect Plug)

Replaceable Plug Insert

- Replaceable in under 2 minutes
- Glass filled nylon material to withstand tough impacts
- Spring wrapped pins to retain a tight fit
- Floating brass pins for secure installation of misaligned sockets
- Pre-injected with dielectric grease for extra corrosion protection
- Recommended Practice: Replace at first signs of corrosion

Molded Interior Plug


- Durable PVC overmold seals inner wires and cable to lock out corrosion
- · Molded wiper rings keep contact pins dry
- Inner pins are also wrapped to retain a tight fit
- Pre-injected with dielectric grease for extra corrosion protection
- Completely sealed against rear entry water intrusion
- Recommended Practice: Clean connection and apply dielectric grease before inserting a new plug insert

Plug Housing

- Unbreakable, non-corrosive nylon housing that resists impact
- Large finger grips for easy coupling/uncoupling
- Recommended Practice: When replacing the insert, pull housing back and clean all connections well

Electrical Cable

- LECTRACOIL[™] Assemblies
 - Excellent recoil memory
 - Resistant to chemicals & abrasion
 - Flexible from -82°F to 195°F (-63°C to 91°C)
- LECTRAFLEX™ Assemblies
 - Resistant to chemicals & abrasion
 - Flexible from -40°F to 150°F (-40°C to 66°C)
- PERMACOIL[™] Assemblies
 - Great recoil memory
 - Resistant to chemicals & abrasion
 - Flexible from -87°F to 150°F (-66°C to 66°C)
- Recommended Practice: Use a tracker bar spring kit or pogo stick to support cable assemblies with longer leads





(L-TSCQCP-ENG) REV2 10-11-16

QCP™ (Quick-Connect Plug) Assemblies

Part No.	Туре	Style	Length
16-125	Replaceable Plug Insert - QCP™ (Quick-Connect Plug)		
22-4324	NON-ABS PERMACOIL™	Coiled	12 Ft.
24-4624	NON-ABS PERMACOIL™	Coiled	15 Ft.
30-4324	ABS PERMACOIL™	Coiled	12 Ft.
30-4624	ABS PERMACOIL™	Coiled	15 Ft.
30-4924	ABS PERMACOIL™	Coiled	15 Ft. with 48" Lead
30-9324	ABS LECTRACOIL™	Coiled	12 Ft.
30-9334	ABS LECTRAFLEX™ QCMS2™	Coiled	12 Ft.
30-9624	ABS LECTRACOIL™	Coiled	15 Ft.
30-9634	ABS LECTRAFLEX™ QCMS2™	Coiled	15 Ft.
30-9924	ABS LECTRACOIL™	Coiled	15 Ft. with 48" Lead
30-9934	ABS LECTRAFLEX™ QCMS2™	Coiled	15 Ft. with 48" Lead
30-9954	ABS LECTRACOIL™	Coiled	20 Ft.
30-2054	ABS LECTRAFLEX™	Straight	12 Ft.
30-2055	ABS LECTRAFLEX™ QCMS2™	Straight	12 Ft.
30-2074	ABS LECTRAFLEX™	Straight	15 Ft.
30-2075	ABS LECTRAFLEX™ QCMS2™	Straight	15 Ft.
30-2095	ABS LECTRAFLEX™ QCMS2™	Straight	20 Ft.
30-2154	ABS LECTRAFLEX™	3-IN-1 Electrical/Air Combo	12 Ft.
30-2155	ABS LECTRAFLEX™ QCMS2™	3-IN-1 Electrical/Air Combo	12 Ft.
30-2174	ABS LECTRAFLEX™	3-IN-1 Electrical/Air Combo	15 Ft.
30-2175	ABS LECTRAFLEX™ QCMS2™	3-IN-1 Electrical/Air Combo	15 Ft.
30-2194	ABS LECTRAFLEX™	3-IN-1 Electrical/Air Combo	20 Ft.
30-2195	ABS LECTRAFLEX™ QCMS2™	3-IN-1 Electrical/Air Combo	20 Ft.
30-2257	ABS LECTRAFLEX™	4-IN-1 Electrical/Air Combo	12 Ft.
30-2274	ABS LECTRAFLEX™	4-IN-1 Electrical/Air Combo	15 Ft.
30-2277	ABS LECTRAFLEX™	4-IN-1 Electrical/Air Combo	15 Ft.
30-2294	ABS LECTRAFLEX™	4-IN-1 Electrical/Air Combo	20 Ft.
30-2297	ABS LECTRAFLEX™	4-IN-1 Electrical/Air Combo	20 Ft.

